



All for better networking.

## AC10U

AC1200 MU-MIMO Dual Band Gigabit WiFi Router





### AC10U

#### AC1200 MU-MIMO Dual Band Gigabit WiFi Router

#### **Product Overview**

AC10U comes with the next generation 802.11ac wave 2.0 WiFi standard delivering up to 1167 Mbps dual-band wireless speed, which is 3 times faster than wireless 11N speed, enabling stable online gaming and 4K streaming from

YouTube and Netflix. With MU-MIMO technology, Beamforming technology, built-in high powered amplifiers and external antennas, AC10U bring long

operating range to fulfill greater home coverage and you will never worry about that you have too many devices to connect. Gigabit

Ethernet ports give you the fastest, most reliable internet

performance. Additionally, Tenda WiFi app and its USB port provide the smartest way to manage your network local and remotely share fun with your family.

#### **Selling Points**

- AC1200 Mbps Wireless
- MU-MIMO
- 3 Gigabit LAN & 1 Gigabit WAN
- 1GHz CPU
- VPN Client and Server

- Dual-Band Wireless
- 4 Omni-directional Antennas
- USB 2.0 Port
- Parental Controls
- WiFi Schedule

## **Selling Points**



#### **Super Experience for Gaming and Streaming**

- With 4 gigabit ports for fast and stable internet connection
- 1GHz CPU for multi-client with responsive performance and fast speed
- USB2.0 port supports making it sharing center of your home



#### **Ultimate Coverage and Stable Performance**

- High power amplifiers for entire-home coverage and eliminating your WiFi dead zones
- MU-MIMO Technology ensures a stable wireless connection and increased quantity of connected clients and data processing
- Beamforming+ technology boosts range for the 802.11ac wave2 WiFi devices
- Four external omni-directionla antennas assure greater home coverage



#### **Smart Management via Tenda App**

- Smart WiFi Schedule can turn on/off WiFi automatically
- Advanced QoS for uninterrupted HD Video streaming
- Power saving and LED control for energy-green household
- Smart Tenda WiFi app for real time management

# **Specification**

### AC10U AC1200 MU-MIMO Dual Band Gigabit WiFi Router

Hardware Specification	
Standards	IEEE802.3; IEEE802.3u
Interface	1*10/100/1000Mbps WAN por 3*10/100/1000Mbps LAN ports 1* USB2.0 port
Antenna	4*6dBi external dual band antennas
Button	1* Reset/WPS button
Power	Input: 100-240V~50/60Hz, 0.6A Output: DC 12V=1.5A
Dimensions	8.66 x 5.57 x 1.93 in (220*141.5*49mm)
Weight	810g/ 1.79lb
LED Indicator	System, Internet, LAN, WiFi/WPS
Wireless Features	
Wireless Standards	IEEE 802.11ac/a/n 5GHz; IEEE 802.11b/g/n 2.4GHz
Data Rate	5GHz: Up to 867Mbps 2.4GHz: Up to 300Mbps
Frequency	Simultaneous dual band 2.4 & 5GHz
Basic Features	SSID Broadcast: Enable/Disable; Transmission Power: high, medium, low,Beamforming, MU-MIMO
wireless Security	WPA-PSK/WPA2-PSK, WPA/WPA2; Wireless Security: Enable/Disable; WPS(WiFi Protected Set-up) fast encryption
Software Features	
Internet Connection Type	PPPoE, Dynamic IP, Static IP PPPoE(Russia), PPTP(Russia), L2TP(Russia) Support auto-sensing internet connection Support PPPOE acount clone
Operating Mode	Wireless Router Mode Universal Repeater Mode WISP Mode AP Mode
DHCP Server	DHCP Server DHCP Client List DHCP Reservation
Virtual Server	Port Forwarding DMZ Host UPnP
Security	Client Filter Parental Control(support black list and white list) Remote Web Management

Firewall Forbit UDP Bood attack Forbit TCP Bood attack Forbit TCP Bood attack Forbit TCP Bood attack Forbit MWAN PING from Internet  DDNS Support DynDNS, No-ip, 3322.org, Oray.com, 88ip  USB Sharing Support Sambal(Storage)/FTP Server  IPsec pass through PPTP pass through PPTP pass through PPTP pass through PPTP server PPTP Client L2TP Client Smart Tarffic Prioritisation Smart WiFi Schedule Smart Power Saving Smart LED on/off Tenda Cloud Tenda App  IPTV Bandwidth Control Guest Network MAC Clone System Log Support automatic access detection Backup & Restore configurations Firmware upgrade online Firmware upgrade online Firmware upgradeable via browser  Others  Others  Others  Operating Temperature: 0°C ~ 40°C Storage Temperature: -40°C ~ 70°C  Humidity Operating Temperature: -40°C ~ 70°C  Humidity Default Access: tendawiri.com Certificates CE, FCC, RoHS  A C1200 MU-MIMO Dual Band Gigabit WiFi Router Power Adapter Install Guide I		
USB Sharing  Support Samba(Storage)/FTP Server  IPSec pass through PPTP pass through PPTP pass through PPTP server PPTP server PPTP server PPTP server PPTP client LZTP client LZTP client Smart Traffic Prioritisation Smart Wiff Schedule Smart Power Saving Smart LED on/off Tenda Cloud Tenda App  IPTV Bandwidth Control Guest Network MAC Clone System Log Support automatic access detection Backup & Restore configurations Firmware upgrade online Firmware upgradeable via browser  Others  Temperature  Operating Temperature: 0°C ~ 40°C Storage Temperature: 40°C ~ 70°C  Humidity  Operating Humidity: 10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing Certificates  CE, FCC, RoHS  AC1200 MU-MIMO Dual Band Gigabit WiFi Router Power Adapter Install Guide	Firewall	Forbid TCP flood attack Forbid flood attack
Peec pass through	DDNS	Support DynDNS, No-ip, 3322.org, Oray.com, 88ip
PPTP pass through L2TP pass through PPTP server PPTP client L2TP client  Smart Traffic Prioritisation Smart WiFi Schedule Smart Dowler Saving Smart LED on/off Tenda Cloud Tenda App  PTV Bandwidth Control Guest Network MAC Clone System Log Support automatic access detection Backup & Restore configurations Firmware upgrade online Firmware upgrade online Firmware upgradeable via browser  Others  Operating Temperature: 0°C ~ 40°C Storage Temperature: -40°C ~ 70°C  Humidity Operating Humidity: 10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing Factory Defaul Settings Default Access: tendawifi.com  Certificates  CE, FCC, RoHS  AC1200 MU-MIMO Dual Band Gigabit WiFi Router Power Adapter Install Guide	USB Sharing	Support Samba(Storage)/FTP Server
Special Features  Smart WiFi Schedule Smart Power Saving Smart LED on/off Tenda Cloud Tenda App  IPTV Bandwidth Control Guest Network MAC Clone System Log Support automatic access detection Backup & Restore configurations Firmware upgrade online Firmware upgradeable via browser  Others  Temperature  Operating Temperature: 0°C ~ 40°C Storage Temperature: -40°C ~ 70°C  Humidity  Operating Humidity: 10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing  Factory Defaul Settings  Default Access: tendawifi.com  Certificates  CE, FCC, RoHS  AC1200 MU-MIMO Dual Band Gigabit WiFi Router Power Adapter Install Guide	VPN	PPTP pass through L2TP pass through PPTP server PPTP client
Others       Bandwidth Control Guest Network MAC Clone System Log Support automatic access detection Backup & Restore configurations Firmware upgrade online Firmware upgrade online Firmware upgradeable via browser         Others         Temperature       Operating Temperature: 0°C ~ 40°C Storage Temperature: -40°C ~ 70°C         Humidity       Operating Humidity:10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing         Factory Defaul Settings       Default Access: tendawifi.com         Certificates       CE, FCC, RoHS         AC1200 MU-MIMO Dual Band Gigabit WiFi Router Power Adapter Install Guide	Special Features	Smart WiFi Schedule Smart Power Saving Smart LED on/off Tenda Cloud
Temperature  Operating Temperature: 0°C ~ 40°C Storage Temperature: -40°C ~ 70°C  Humidity  Operating Humidity: 10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing  Factory Defaul Settings  Default Access: tendawifi.com  Certificates  CE, FCC, RoHS  AC1200 MU-MIMO Dual Band Gigabit WiFi Router Power Adapter Install Guide	Others	Bandwidth Control Guest Network MAC Clone System Log Support automatic access detection Backup & Restore configurations Firmware upgrade online
Humidity  Operating Humidity:10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing  Factory Defaul Settings  Default Access: tendawifi.com  Certificates  CE, FCC, RoHS  AC1200 MU-MIMO Dual Band Gigabit WiFi Router Power Adapter Install Guide	Others	
Factory Defaul Settings  Default Access: tendawifi.com  Certificates  CE, FCC, RoHS  AC1200 MU-MIMO Dual Band Gigabit WiFi Router Power Adapter Install Guide	Temperature	
Certificates  CE, FCC, RoHS  AC1200 MU-MIMO Dual Band Gigabit WiFi Router Power Adapter Install Guide	Humidity	Operating Humidity:10% ~ 90% RH non-condensing Storage Humidity: 5% ~ 90%RH non-condensing
AC1200 MU-MIMO Dual Band Gigabit WiFi Router Power Adapter Install Guide	Factory Defaul Settings	Default Access: tendawifi.com
Package Contents Power Adapter Install Guide	Certificates	CE, FCC, RoHS
	Package Contents	Power Adapter Install Guide

#### SHENZHEN TENDA TECHNOLOGY CO.,LTD.

Tenda Technology Bldg.Int' IECity, # 1001 Zhong Shan Yuan Rd.,Nanshan District,Shenzhen China.

E-mail:suppor t@tenda.com.cn Tel:+86-755-2765 7098 Fax:+86-755-2765 7178 PC:518055



